

TECHNICAL DATASHEET

Exterior diesel screed machine X-PRO D200 | ref.40095



Thermal engine machine for pumping products such as liquid screed or for spraying shotcrete. Very powerful, it is designed for large construction sites.

Made in our Spanish factory, it is equipped with a button control panel for simplified use, motor and hydraulic pump with adjustable flow-rate.

Motor	Kohler KDI 1903
Motor power	36 kW
Oil	10W40
Fuel	Road B7 Diesel
Diesel tank	41,5 L
Cooling	liquid
Speed of rotation	2600 RPM
Number of cylinders	3
Consumption	8,5 L/h
Hydraulic system	50 L
Engine monitoring panel	complete
Hydraulic controls	electrical/manual
Pump speed setting	manual
Automatic accelerator control	electrical/manual
Hopper tank capacity	220 L
Tank drain plug	yes
Variable flow	up to 25 m ³ /h
Hydraulic pressure	from 0 to 210 bar
Pump pressure	from 0 to 30 bar
Maximum grain size	up to 12 mm
Pump	2L8
Pump reverse operation	yes
HP washer max pressure	140 bar
HP washer flow-rate	11 L/min
Overall length with tow bar	4,26 m
Overall length without tow bar	3,01 m
Overall width	1,50 m
Height at the highest point	1,59 m
Weight when full with oil and diesel	1160 kg
Delivery height	100 m
Max. hose length	200 m

Delivered with

- a Ø50 x 20 m hose
- two cleaning balls Ø60
- a grease pump with a grease cartridge
- a complete high pressure washer lance
- a 10 m high pressure washer hose
- a storage carry-case