



TECHNICAL DATASHEET

MIXPRO 28 - 3 KW FLOOR-SCREED / REF.30718

CONTINUOUS MIXING MACHINE



Easy-to-use continuous mixing pump with a high yield.

It can be disassembled in 4 parts, without tools, for a simplified transport.

APPLICATIONS

Floor screed, plaster, air insulation, fireproof products, light powders (polystyrene) ...

Products with instant kneading and no need for rest time.

Tank capacity	70 L
Electrical supply	230 V - 50 Hz
Thermal protection	yes
Geared-motor driving mixing arm	3 kW
Variable speed	yes
Water pump	yes
Flow-meter	digital display
Water safety switch	yes
Product pressure	0 to 20 bar
Product flow-rate	up to 26 L/min
Rotor/stator	MIXER 32 - 26 L/min
Pouring yield	40 bags of 25 kg/h
Pouring max. hose length	100 m
Loading height	102 cm
Dimensions (L x w x h)	100 x 76 x 159 cm
Weight	124 kg

DELIVERED WITH

- a Ø25 x 15 m product hose
- a Ø19 x 20 m water hose with GEKA
- a Ø19 x 2 m pouring hose
- a 21 m electrical remote control
- an unplugging key
- a mounting spray for rotor/stator
- two cleaning balls

