



TECHNICAL DATASHEET

X-PRO D140 / REF.40090

LIQUID SCREED MACHINE

Thermal engine machine for pumping products such as liquid screed or for spraying shotcrete.

Made in our Spanish factory, it is equipped with a button control panel for simplified use, an automatic accelerator, motor and hydraulic pump with adjustable flow-rate.



Motor	Kohler KDW 1404
Motor power	19 kW - stage V
Oil	5W40 synthetic
Fuel	Diesel B7
Diesel tank	29 L
Cooling	liquid
Speed of rotation	2600 RPM
Number of cylinders	4
Consumption	6,2 L/h
Hydraulic system	40 L
Engine monitoring panel	complete
Hydraulic controls	electrical/manual
Pump speed setting	manual
Automatic accelerator control	electrical/automatic
Hopper tank capacity	218 L
Tank drain plug	yes
Variable flow	from 0 to 230 L/min (14 m3/h)
Hydraulic pressure	from 0 to 140 bar
Pump pressure	from 0 to 30 bar
Maximum grain size	up to 10 mm
Pump	60R12
Pump reverse operation	yes
HP washer max pressure	140 bar
HP washer flow-rate	11 L/min
Overall length with tow bar	3,66 m
Overall length without tow bar	3,28 m
Overall width	1,24 m
Height at the highest point	1,28 m
Weight when full with oil and diesel	720 kg
Delivery height	80 m
Max. hose length	120 m

DELIVERED WITH

- a Ø50 x 20 m hose
- a 22 m wired remote control
- two cleaning balls Ø60
- a grease pump with a grease cartridge
- a complete high pressure washer lance
- a 10 m high pressure washer hose
- a storage carry-case

**Made in
Spain**